

# PLASMA CUTTING

The new series of Torches  
**Hybrid** with **EASY FIT**

A revolutionary solution to save time and money

TEC.MB.  
=  
Quality  
Technology  
Innovation



Registered Community Design

Hand Torches for Heavy-Duty application, with **EASYFIT** connection (Patent Pending)



**Quality  
Technology  
Innovation**

Torches with standard spare parts. See the UPH torches catalog

- UPH-105L** No high frequency start 105A
- 05831LA Hand torch Heavy-Duty **UPH-105L** 15° 130cm (52"), EASYFIT connection
  - 05831LB Hand torch Heavy-Duty **UPH-105L** 15° 80cm (31"), EASYFIT connection
  - 05831LC Hand torch Heavy-Duty **UPH-105L** 90° 130cm (52"), EASYFIT connection
  - 05831LD Hand torch Heavy-Duty **UPH-105L** 90° 80cm (31"), EASYFIT connection
- UPH-125L** No high frequency start 125A
- 05931LA Hand torch Heavy-Duty **UPH-125L** 15° 130cm (52"), EASYFIT connection
  - 05931LB Hand torch Heavy-Duty **UPH-125L** 15° 80cm (31"), EASYFIT connection
  - 05931LE Hand torch Heavy-Duty **UPH-125L** 45° 130cm (52"), EASYFIT connection
  - 05931LF Hand torch Heavy-Duty **UPH-125L** 45° 80cm (31"), EASYFIT connection
  - 05931LC Hand torch Heavy-Duty **UPH-125L** 90° 130cm (52"), EASYFIT connection
  - 05931LD Hand torch Heavy-Duty **UPH-125L** 90° 80cm (31"), EASYFIT connection
- UPH-160L** No high frequency start 160A
- 03931LC Hand torch Heavy-Duty **UPH-160L** 45° 130cm (52"), EASYFIT connection
  - 03931LD Hand torch Heavy-Duty **UPH-160L** 45° 80cm (31"), EASYFIT connection
  - 03931LA Hand torch Heavy-Duty **UPH-160L** 90° 130cm (52"), EASYFIT connection
  - 03931LB Hand torch Heavy-Duty **UPH-160L** 90° 80cm (31"), EASYFIT connection

**Extensions and Leads, Coaxial Cable**

|              |                     |                        |                           |
|--------------|---------------------|------------------------|---------------------------|
| 05286FX-L    | Extension 7.5m,     | Female EASYFIT 6pins - | Male EASYFIT 6pins        |
| 05288FX-L    | Extension 15m,      | Female EASYFIT 6pins - | Male EASYFIT 6pins        |
| 09782FX-L ** | Lead assembly 7.5m, | Female EASYFIT 6pins - | Male EURO CONNECTOR 6pins |
| 09787FX-L ** | Lead assembly 15m,  | Female EASYFIT 6pins - | Male EURO CONNECTOR 6pins |
| 05286FX-HY1  | Lead assembly 7.5m, | Female EASYFIT 6pins - | Male HY H-105 connection  |
| 05288FX-HY1  | Lead assembly 15m,  | Female EASYFIT 6pins - | Male HY H-105 connection  |
| 05286FX-HY2  | Lead assembly 7.5m, | Female EASYFIT 6pins - | Male HY H-125 connection  |
| 05288FX-HY2  | Lead assembly 15m,  | Female EASYFIT 6pins - | Male HY H-125 connection  |

\*\* Connection to the system to be confirmed on the purchase order